

Model	 =Electric	 =Engine	JCPT1418DC	JCPT1418RT
-------	---	---	------------	------------

Size				
Max. Working Height	14.30m			
Max. Platform Height	12.30m			
Overall Length(With/Without Outriggers)	3.84m/3.19m			
Overall Width	1.76m			
Overall Height(Rails Up)	2.74m			
Overall Height(Rails Down)	1.97m			
Platform Size(Length×Width)	2.88×1.52m			
Platform Extension Size	1.43m			
Ground Clearance(Raised/Stowed)	0.24			
Wheelbase	2.29m			
Turning Radius(Inside/Outside)	2.15m/4.85m			
Tyres	26×12-16.5			

Performance				
S.W.L	363kg			
S.W.L On Extension	136kg			
Max. Occupants	3			
Gradeability	40%			
Max. Working Slope	2°/3°			
Up/Down Speed	45/46sec			
Travel Speed(Raised)	0.48km/h			
Travel Speed(Stowed)	6.0km/h	5.20km/h		

Weight				
Overall Weight(With/Without Outriggers)	5150kg	5050kg		

Power				
Diesel Engine	Kubota D1105	/	18.6kW/2400rpm	
Diesel Tank	/	47L		
Hydraulic Tank	71L	71L		
Battery	8×6V/315Ah	/		
Charger	48V/25A	/		
Driving Motor	2×32VAC/3.3kW	/		
Lifting Motor	48V/3.8kW	/		

Other Configurations					
4×4 Driving(RT)	4×2 Driving(DC)	Swing-out Engine Tray(RT)	Oscillating Axle	Forklift Pockets	Drivable At Full Height

Model	 =Electric	 =Engine	JCPT1218DC	JCPT1218RT
-------	---	---	------------	------------

Size				
Max. Working Height	12.00m			
Max. Platform Height	10.00m			
Overall Length(With/Without Outriggers)	3.84m/3.19m			
Overall Width	1.76m			
Overall Height(Rails Up)	2.59m			
Overall Height(Rails Down)	1.82m			
Platform Size(Length×Width)	2.88×1.52m			
Platform Extension Size	1.43m			
Ground Clearance(Raised/Stowed)	0.24			
Wheelbase	2.29m			
Turning Radius(Inside/Outside)	2.15m/4.85m			
Tyres	26×12-16.5			

Performance				
S.W.L	454kg			
S.W.L On Extension	136kg			
Max. Occupants	4			
Gradeability	40%			
Max. Working Slope	2°/3°			
Travel Speed(Raised)	0.48km/h			
Travel Speed(Stowed)	6.0km/h	5.20km/h		
Up/Down Speed	40/46sec	38/46sec		

Weight				
Overall Weight(With/Without Outriggers)	4400kg/4135kg	4300kg/3900kg		

Power				
Diesel Engine	Kubota D1105	/	18.6kW/2400rpm	
Diesel Tank	/	47L		
Hydraulic Tank	71L	71L		
Battery	8×6V/315Ah	/		
Charger	48V/25A	/		
Driving Motor	2×32VAC/3.3kW	/		
Lifting Motor	48V/3.8kW	/		

Other Configurations					
4×4 Driving(RT)	4×2 Driving(DC)	Swing-out Engine Tray(RT)	Oscillating Axle	Forklift Pockets	Drivable At Full Height